

SAFETY DATA SHEET

according to Regulation (EU) No. 453/2010

Primus Power Gas Primus Summer Gas Primus Winter Gas

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product code 2202, 2206, 2207

Synonyms None.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Fuel

Substance/Preparation

1.3. Details of the supplier of the safety data sheet

Company/UndertakingPrimus ABIdentificationBox 6041

SE-171 06 SOLNA, Schweden

www.primus.se

Telefon +46-8-564 842 30 Telefax +46-8-564 842 40

info@primus.se

1.4. Emergency telephone

number

+46-8-564 842 30

Issuing date 20.08.2014

Version GHS 2

2. Hazards identification

2.1. Classification of the substance or mixture

Classification according to **Regulation (EC) No. 1272/2008**

(GHS/CLP)

Flammable gases, Cat. 1, H220

Compressed gas, H280

Classification according to EU Directives 67/548/EEC or

1999/45/EC

F+; R12

Additional information For the full text of the phrases mentioned in this Section, see

Section 16.

2.2. Label elements





Signal Word Danger

Hazard Statements H220: Extremely flammable gas.

H280: Contains gas under pressure; may explode if heated.

P101: If medical advice is needed, have product container or label **Precautionary statements**

at hand.

P102: Keep out of reach of children.

P210b: Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P377: Leaking gas fire: Do not extinguish, unless leak can be

stopped safely.

P381: Eliminate all ignition sources if safe to do so.

P410+P403: Protect from sunlight. Store in a well-ventilated place.

Additional advice None.

GHS product identifier Hydrocarbons, C3-4-rich, petroleum distillate (<0.1% 1,3-

butadiene), CAS-No. 68512-91-4, EC-No. 270-990-9

Labelling according to Directives 67/548/EEC or 1999/45/EC



F+ - Extremely flammable.

R-phrase(s) R12: Extremely flammable.

S-phrase(s) S2: Keep out of the reach of children.

S9: Keep container in a well-ventilated place.

S16: Keep away from sources of ignition - No smoking.

Hazardous component(s) which must be listed on the label

None.

2.3. Other hazards Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Also after use, do not open with force or burn. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep away from children.

3. Composition/information on ingredients

Components		CLP Classification	DSD/DPD Classification	Product identifier
Hydrocarbons, C3-4- rich, petroleum distillate (<0.1% 1,3-butadiene)	100 %	Flam. Gas 1 H220, Press. Gas H280	F+; R-12	CAS-No.: 68512-91-4 EC-No.: 270-990-9
Furan-2-methanthiol	20 ppm	Flam. Liq. 3 H226	; R-10	CAS-No.: 98-02-2 EC-No.: 202-628-2

For the full text of the phrases mentioned in this Section, see Section 16.

Hazardous impurities

None known.

4. First aid measures

4.1. Description of first aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. Medical

examination necessary even only on suspicion of intoxication. Persons who have inhaled the gas or fumes produced in a fire or who have come into contact with the substance may not show immediate symptoms. They should be taken to a doctor with this card. Patient must be kept under medical supervision for at least 24

hours.

Skin contact May cause frostbite. Wash off immediately with plenty of water.

Remove contaminated clothing and shoes. Consult a physician for

severe cases.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for

at least 15 minutes. Call a physician immediately.

Ingestion Rinse mouth. Drink 1 or 2 glasses of water. Do not induce vomiting.

Medical examination necessary even only on suspicion of

intoxication.

4.2. Most important symptoms and effects, both acute and

delayed

Contact can cause cold burns, frostbite and/or chemical burns with severe skin damage. Symptoms of poisoning may only appear several hours later. Inhalation may provoke the following symptoms:

Asphyxia.

4.3. Indication of any immediate medical attention and special treatment needed

Artificial respiration and/or oxygen may be necessary.

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2). Water mist

Extinguishing media which must not be used for safety reasons

High volume water jet.

5.2. Special hazards arising from the substance or mixture

Extremely flammable. Pay attention to the spreading of gases especially at ground level (heavier than air) and to the direction of the wind. Closed containers may explode due to pressure build-up when subjected to excessive heat or intense fire.

5.3. Advice for firefighters

Special protective equipment for firefighters

In the event of fire, wear self-contained breathing apparatus.

Complete suit protecting against chemicals.

Specific methods Do not use a solid water stream as it may scatter and spread fire.

Water mist may be used to cool closed containers. Prevent fire extinguishing water from contaminating surface water or the ground

water system.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Advice for non-emergency Use personal protective equipment. Avoid

Use personal protective equipment. Avoid contact with skin and eyes. Remove all sources of ignition. Pay attention to flashback.

Pay attention to the spreading of gases especially at ground level

(heavier than air) and to the direction of the wind.

Advice for emergency

responders

personnel

Keep people away from and upwind of spill/leak. Remove all sources of ignition. Pay attention to flashback. Ventilate the area.

Pay attention to the spreading of gases especially at ground level

(heavier than air) and to the direction of the wind.

6.2. Environmental precautions No special environmental precautions required.

6.3. Methods and material for containment and cleaning up

Ventilate the area.

6.4. Reference to other sections See chapter 8 and 13.

7. Handling and storage

7.1. Precautions for safe

handling

Wear personal protective equipment. Provide appropriate exhaust ventilation at machinery. Keep away from heat and sources of ignition. Pressurized container. Protect from sunlight and do not

expose to temperatures exceeding 50 °C.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool and shaded area. Store in a place accessible by authorized persons only. Keep away from heat. Keep away from

direct sunlight.

7.3. Specific end use(s) See chapter 13.

8. Exposure controls/personal protection

8.1. Control parameters

Exposure limit(s) This information is not available.

Propane (CAS 74-98-6)

Ireland - Occupational Exposure

Limits - TWAs

Butane (CAS 106-97-8)

Ireland - Occupational Exposure

Limits - TWAs

United Kingdom - Workplace Exposure Limits (WELs) - STELs United Kingdom - Workplace Exposure Limits (WELs) - TWAs

1000 ppm TWA

1000 ppm TWA

750 ppm STEL 1810 mg/m3 STEL 600 ppm TWA 1450 mg/m3 TWA

8.2. Exposure controls

Occupational exposure controls Handle in accordance with good industrial hygiene and safety

practice. Ensure adequate ventilation, especially in confined areas.

General industrial hygiene practice.

Personal protection equipment

In case of good ventilation no personal respiratory protective Respiratory protection

> equipment required. In case of insufficient ventilation wear suitable respiratory equipment. Respirator with filter for organic vapour

Hand protection No special measures required.

Eye protection Safety glasses with side-shields.

Skin and body protection Long sleeved clothing.

Thermal hazards Keep product and empty container away from heat and sources of

ignition.

Environmental exposure controls No special measures required.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form Compressed liquefied gas.

ColourColourless.OdourCharacteristic.

Odour Threshold

pH:

No information available.

No information available.

No information available.

No information available.

15 °C at atmospheric pressure

Flash point:

No information available.

Evaporation Rate:No information available.
Flammability:
No information available.

Explosion limits: 1.8 % - 10.2 %

Vapour pressure: 2.8 bar @ 15 °C / 8.3 bar 50 °C

Vapor density:No information available.

Relative density: 0.5 kg/l @ 20 °C

Water solubility:

Partition coefficient (n
No information available.

No information available.

octanol/water):

Autoignition temperature: 400 °C

Decomposition temperature:Viscosity:
No information available.
No information available.

Combustion/explosion hazards: Liquefied gas under pressure, flammable

Oxidizing properties: None

9.2. Other information

General Product Characteristics No information available.

10. Stability and reactivity

10.1. Reactivity Risk of receptacle bursting.

10.2. Chemical stability Stable under recommended storage conditions.

10.3. Possibility of hazardous

reactions

No information available.

10.4. Conditions to avoid Heat, flames and sparks. Temperatures above 50 °C.

10.5. Incompatible materials None.

10.6. Hazardous decomposition

products

Carbon monoxide, carbon dioxide and unburned hydrocarbons

(smoke).

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity Hydrocarbons, C3-4-rich, petroleum distillates (CAS 68512-91-

4)

Inhalation LC50 Rat = 658 mg/L 4 h (IUCLID)

Propane (CAS 74-98-6)

Inhalation LC50 Rat = 658 mg/L 4 h (IUCLID)

Butane (CAS 106-97-8)

Inhalation LC50 Rat = 658 g/m3 4 h (NLM_CIP)

Isobutane (CAS 75-28-5)

Inhalation LC50 Rat = 658 mg/L 4 h (IUCLID)

Skin corrosion/irritationNo skin irritation.

Serious eye damage/eye

irritation

No eye irritation.

Respiratory / Skin Sensitisation None.

Carcinogenicity Based on available data, the classification criteria are not met.

Germ cell mutagenicity Classification not possible from current data.

Reproductive toxicity Classification not possible from current data.

Specific target organ toxicity

(single exposure)

No data available.

Specific target organ toxicity

(repeated exposure)

No data available.

Aspiration hazard No data available.

Human experience No data available.

Information on likely routes of

exposure

inhalativ

Symptoms related to the physical, chemical and toxicological characteristics

Contact can cause cold burns, frostbite and/or chemical burns with

severe skin damage. Inhalation may provoke the following

symptoms: Tiredness Drowsiness

Other information Gas reduces oxygen available for breathing.

12. Ecological information

12.1. Toxicity No data is available on the product itself.

12.2. Persistence and

degradability

The product is degraded in the atmosphere.

12.3. Bioaccumulative potential Bioaccumulation is unlikely.

12.4. Mobility in soilMay evaporate quickly. Decomposes rapidly in contact with light.

12.5. Results of PBT and vPvB

assessment

No information available.

12.6. Other adverse effectsNo information available.

13. Disposal considerations

13.1. Waste treatment methods

Waste from residues / unused

products

EWC waste disposal No: 16 05 04 - Gase in Druckbehältern. Dispose of as hazardous waste in compliance with local and national regulations. Pressurized container. Protect from sunlight

and do not expose to temperatures exceeding 50 °C.

Contaminated packaging Dispose of as unused product. Container hazardous when empty.

14. Transport information

ADR/RID Proper shipping name RECEPTACLES, SMALL, CONTAINING

GAS

UN No 2037. Class 2.

ADR/RID-Labels 2.1. Classification code 5F.

Risk No. 23.

Limited quantity 120 ml.

Tunnel code D

IMDG Proper shipping name Receptacles, small, containing gas without a

release device, non refillable

UN No 2037. Class 2. Packing group -. IMDG-Labels 2.1.

Limited quantity Siehe SV277.

Marine Pollutant no

IATA Proper shipping name Receptacles, small, containing gas

(flammable) without a release device, non-refillable

UN No 2037. Class 2.1. IATA label 2.1.

Packing instruction (passenger aircraft): 203 (1 kg).

Packing instruction (LQ): -.

Packing instruction (cargo aircraft): 200 (15 kg).

Further Information None.

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulatory Information The product is classified and labelled according to Regulation (EC)

No. 1272/2008 (GHS/CLP).

Hydrocarbons, C3-4-rich, petroleum distillates (CAS 68512-91-4)

EU - REACH (1907/2006) - Annex XVII - Restrictions on Certain

Use restricted. See item 28. Use restricted. See item 29.

Dangerous Substances

EU - REACH (1907/2006) - List of

Present

Registered Substances Propane (CAS 74-98-6)

EU - REACH (1907/2006) - List of

Registered Substances

Present

UN (United Nations) - Selected Volatile Substances Prone to

Present

Abuse

Butane (CAS 106-97-8)

EU - REACH (1907/2006) - Annex XVII - Restrictions on Certain

Use restricted. See item 28. Use restricted. See item 29.

Dangerous Substances

EU - REACH (1907/2006) - List of

Registered Substances

Present

UN (United Nations) - Selected Volatile Substances Prone to

Present

Abuse

Isobutane (CAS 75-28-5)

EU - REACH (1907/2006) - Annex XVII - Restrictions on Certain

Dangerous Substances

Use restricted. See item 29.

Use restricted. See item 28.

EU - REACH (1907/2006) - List of

Registered Substances

UN (United Nations) - Selected

Volatile Substances Prone to

Abuse

Present

Present

15.2. Chemical safety

assessment

Not required.

16. Other information

Revision Note Safety datasheet sections which have been updated: 2, 15.

Key or legend to abbreviations

and acronyms

CLP: Classification according to Regulation (EC) No. 1272/2008

(GHS/CLP)

Key literature references and

sources for data

According to information supplied by the manufacturer.

Classification procedure Calculation method.

Full text of phrases referred to under sections 2 and 3

H220: Extremely flammable gas. H226: Flammable liquid and vapour.

H280: Contains gas under pressure; may explode if heated.

Primus Power Gas / Primus Summer Gas /

Primus Winter Gas Print Date 20.08.2014 9/10

R12: Extremely flammable.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release. This safety datasheet only contains information relating to safety and does not replace any product information or product specification.